


This chain is based on S roller type conveyor chain, and has flanged side rollers installed on extended pins on both sides. It is engaged with the sprockets at the central rollers, and runs using the side rollers. It can be manufactured by using the same materials as those of a regular conveyor chain.

When you order:

Please specify the name of series, version symbol and the installation intervals of side rollers.

Application

1. When plates are specially shaped to accommodate such devices as dogs or top plates.
2. When the chain cannot support the load by its central rollers only.
3. To stably convey articles with high in gravity center.
4. To install chain float prevention guides.



Chain No.	Pitch P	Roller Diameter R	W	Plate		Side Roller			K	Z	Side Roller (kg/EA)	Rail Intervals	Side Roller Allowable Load
				H	T	A	B	G					
03075 - S	75	15.9	16.1	22	3.2	31.8	42	12	76	38	0.3	70	110
03100 - S	100	15.9	16.1	22	3.2	31.8	42	12	76	38	0.3	70	110
430 - S	101.6	20.1	22.6	25.4	4.8	38.1	50	15	103	56	0.5	100	160
05075 - S	75	22.2	22	32	4.5	40	50	14	102	55	0.5	120	200
05100 - S	100	22.2	22	32	4.5	40	50	14	102	55	0.5	120	200
05150 - S	150	22.2	22	32	4.5	40	50	14	102	55	0.5	120	200
450 - S	101.6	22.2	27	28.6	6.3	44.5	55	20	130	70.5	0.7	170	240
10100 - S	100	29	30	38.1	6.3	50.8	65	20	136	73	1.0	200	330
10150 - S	150	29	30	38.1	6.3	50.8	65	20	136	73	1.0	200	330
6205 - S	152.4	34.9	37.1	44.5	7.9	57.2	70	25	167	90.5	1.3	280	470
12200 - S	200	34.9	37.1	44.5	7.9	65	80	24	167	92.5	1.8	280	470
12250 - S	250	34.9	37.1	44.5	7.9	65	80	24	167	92.5	1.8	280	470
17200 - S	200	40.1	51.4	50.8	9.5	65	80	24	192	112.5	3.8	320	540
17250 - S	250	40.1	51.4	50.8	9.5	65	80	24	192	112.5	3.8	320	540
17300 - S	300	40.1	51.4	50.8	9.5	65	80	24	192	112.5	3.8	320	540
26200 - S	200	44.5	57.2	63.5	9.5	80	100	34	229	124.5	6.9	500	860
26250 - S	250	44.5	57.2	63.5	9.5	80	100	34	229	124.5	6.9	500	860
26300 - S	300	44.5	57.2	63.5	9.5	80	100	34	229	124.5	6.9	500	860
36250 - S	250	50.8	66.7	76.2	12.7	100	125	38	268	151	11.7	670	1130
36300 - S	300	50.8	66.7	76.2	12.7	100	125	38	268	151	11.7	670	1130
36450 - S	450	50.8	66.7	76.2	12.7	100	125	38	268	151	11.7	670	1130