



chain no.	Pitch	Roller diameter	Width between inner plates	Pin diameter	Pin length		Inner plate depth	Plate thickness	Ultimate tensile strength	Average tensile strength	Weight per meter
	P	d1 max	b1 min	d2 max	L max	Lc max	h2 max	T max	Q min.	Q <sub>0</sub>	q
	mm	mm	mm	mm	mm	mm	mm	mm	kN/LB	kN	kg/m
428H XR	12.700	8.51	7.94	4.45	21.70	22.70	12.30	2.20	22.0/4946	23.00	0.85
520H XR	15.875	10.16	6.35	5.24	21.52	22.00	14.15	2.40	34.0/6840	35.00	1.00
525H XR	15.875	10.16	7.94	5.24	23.80	25.20	15.09	2.40	34.0/6840	35.00	1.12
530H XR	15.875	10.16	9.60	5.24	25.40	26.80	15.09	2.40	34.0/6840	35.00	1.20

■ X-ring chains are specially designed for use on high powered as well as touring bikes. With a special 4-lips seal ring, lubrication is safely sealed inside the chain during its lifetime. With low frictional resistance, X-ring chains operate much softer and cooler, and engage better than traditional O-ring chain. At the same time, X-ring considerably increases the lifetime of the chain as well. Outer plate colors available: golden, silver. Painted plate colors available: red, yellow, orange, green, blue.

